


Installation



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Lofty **Backing** GlasBac™

Product Specifications


Product Number:	1272302500
Product Construction:	Tufted Pattern Loop
Standard Colorline:	11
Yarn System:	100% Recycled Content Type 6 Nylon
Yarn Manufacturer:	Aquafil
Dye Method:	100% Solution Dyed
Recycled Content:	
Post Industrial Range:	64% - 64%
Post Consumer:	12%
Total Recycled Content:	76% - 76%
Soil/Stain Protection:	Protekt ²
Antimicrobial:	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept®

	Imperial	Metric
Tufted Yarn Weight:	28 oz/yd ²	949.0 g/m ²
Machine Gauge:	1/10 in	39.4 ends/10 cm
Pile Height:	0.24 in	6.1 mm
Pile Thickness:	0.190 in	4.8 mm
Stitches	7.30 /in	28.74 ends/10 cm
Pile Density:	7855	
Traffic Classification:	Heavy	
Fiber Modification Ratio:	1.9 To 2.2	
Size:	19.69 in X 19.69 in	50 cm X 50 cm

Performance Specifications

Radiant Panel:	(ASTM E-648) Class 1
Smoke Density:	(ASTM E - 662) ≤450
Lightfastness:	(AATCC 16 - E) ≥ 4.0 @ 60 Afu's
Static:	(AATCC - 134) < 3.0 Kv
Dimensional Stability:	AACHEN Din 54318 <.10%
Flammability:	Passes Methenamine Pill Test (Doc-Ff1-70)
Standard Backing:	GlasBac Tile
Backing Options:	GlasBac Tile, GlasBacRE Tile, CushionBac Renew™ Tile

Installation



All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.

Product Lofty **Backing** GlasBac™

Product Specifications

Product Number:	1272302000
Product Construction:	Tufted Pattern Loop
Standard Colorline:	11
Yarn System:	100% Recycled Content Type 6 Nylon
Yarn Manufacturer:	Aquafil
Dye Method:	100% Solution Dyed
Recycled Content:	
Post Industrial Range:	64% - 64%
Post Consumer:	12%
Total Recycled Content:	76% - 76%
Soil/Stain Protection:	Protekt ²
Antimicrobial:	(AATCC 138 Washed) (AATCC 174 Parts 2&3) Intersept®

	Imperial	Metric
Tufted Yarn Weight:	28 oz/yd ²	949.0 g/m ²
Machine Gauge:	1/10 in	39.4 ends/10 cm
Pile Height:	0.24 in	6.1 mm
Pile Thickness:	0.190 in	4.8 mm
Stitches	7.30 /in	28.74 ends/10 cm
Pile Density:	7855	
Traffic Classification:	Heavy	
Fiber Modification Ratio:	1.9 To 2.2	
Size:	39.37 in X 39.37 in	1 m X 1 m

Performance Specifications

Radiant Panel:	(ASTM E-648) Class 1
Smoke Density:	(ASTM E - 662) ≤450
Lightfastness:	(AATCC 16 - E) ≥ 4.0 @ 60 Afu's
Static:	(AATCC - 134) < 3.0 Kv
Dimensional Stability:	AACHEN Din 54318 <.10%
Flammability:	Passes Methenamine Pill Test (Doc-Ff1-70)
Standard Backing:	GlasBac Tile
Backing Options:	GlasBac Tile, GlasBacRE Tile, CushionBac Renew™ Tile