

Installation Method



Quarter turn

Ashlar

Monolithic



Brick

Non Directional

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, [please see our full LVT product disclaimer](#).

Product Specifications

Product Number	C003
Product Construction	Luxury Vinyl Tile
Class / ASTM F1700	Class III Printed Vinyl Tile
Wear Layer Thickness	22 mil
Total Thickness	3.0 mm
Backing Class	Commercial Grade
Finish	Ceramor™ Coating
Nominal Dimensions	50cm x 50cm (19.69 in x 19.69 in)

Performance Specifications

Slip Resistance	(ASTM D2047) >0.55 wet/dry, ADA Compliant
Static Load Limit	(ASTM F970) 1500 psi
Flexibility	(ASTM F137) Passes
Resistance to Heat	(ASTM F1514) Passes
Resistance to Light	(ASTM F1515) Passes
Radiant Flux	(ASTM E648) Class I
Smoke Density	(ASTM E 662) < 450
Size & Squareness	(ASTM F2055) Passes
Thickness	(ASTM F386) Passes
Dimensional Stability	(ASTM F2199) Passes
Residual Indentation	(ASTM F1914) Passes
Resistance to Chemicals	(ASTM F925) Passes

Health + Environmental Specifications

Carbon Offsets	Carbon Neutral Floors™
Indoor Air Quality	GREENGUARD Gold FloorScore® CDPH 01350 compliant
Material Composition	Free of Ortho Phthalates, Added Formaldehyde and Heavy Metal Stabilizers
Disclosure of Environmental Impacts	Environmental Product Declaration
Disclosure of Product Ingredients	Health Product Declaration Pending
Environmental Certifications	NSF/ANSI 332 Silver
LEED v4	Contributes to IEQ: Low Emitting Materials; M&R: EPD and EPR
End of Life	Fully Recyclable into Carpet Tile Backing through ReEntry®

Packaging

Quantity per Carton	37.67 sq. ft. (3.5 m²)
Pieces per Carton	14
Weight per Carton	19.0 kg (42 lbs)
Cartons per Pallet	44
Pallets per Truckload	20

Technical Information

Installation	Interface LVT Installation Guidelines
Maintenance	Interface LVT Maintenance Guidelines
Reclamation	Recyclable through ReEntry® - Call 1.888.733.6873 (U.S.) / 1.866.398.3191 (Canada)
Warranty	15 Year Standard LVT Warranty - US / LATAM 15 Year Standard LVT Warranty - Canada