

Interface

Deeply Rooted

PRODUCT NUMBER:	141720AK00
PRODUCT CONSTRUCTION:	Tufted Pattern Loop
STANDARD COLORLINE:	8
YARN SYSTEM:	Post-Consumer Content Nylon
YARN MANUFACTURER:	Universal
DYE METHOD:	100% Solution Dyed
RECYCLED CONTENT:	
Post Industrial:	71% - 71%
Post Consumer:	1%
Total Recycled Content:	72% - 72%
SOIL/STAIN PROTECTION:	Protekt ² @
PRESERVATIVE PROTECTION:	Intersept@
INDOOR AIR QUALITY:	Green Label Plus #GLP0820,CDPH01350

PRODUCT SPECIFICATIONS	IMPERIAL	METRIC
TUFTED YARN WEIGHT:	24 oz/yd ²	814.0 g/m ²
MACHINE GAUGE:	1/10 in	39.4 ends/cm
PILE HEIGHT:	0.17 in	4.3 mm
PILE THICKNESS:	0.106 in	2.7 mm
STITCHES:	8.00 /in	31 ends/10 cm
PILE DENSITY:	8,151 oz/yd ³	302,237.3 g/m ³
TRAFFIC CLASSIFICATION:	Heavy	
FIBER MODIFICATION RATIO:	1.7 to 1.9	
SIZE:	9.845 in x 39.38 in	25 cm x 1 m

PERFORMANCE SPECIFICATIONS

Radiant Panel:	(ASTM E-648) Passes
Smoke Density:	(ASTM E - 662) ≤ 450
Lightfastness:	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static:	(AATCC - 134) < 3.0 KV
Dimensional Stability:	AACHEN Din 54318 <.10%
Flammability:	Passes Methenamine Pill Test (DOC-FF1-70)
Standard Backing:	GlasBac® Tile
Backing Options:	GlasBac® Tile, GlasBac® RE Tile, CushionBac Renew™ Tile

INSTALLATION

Installation Method	Ashlar, Herringbone
---------------------	---------------------

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.