

Interface

DL901

PRODUCT NUMBER:	1500202500
PRODUCT CONSTRUCTION:	Tufted Pattern Loop
STANDARD COLORLINE:	2
YARN SYSTEM:	100% Recycled Content Nylon
YARN MANUFACTURER:	Aquafil
DYE METHOD:	100% Solution Dyed
RECYCLED CONTENT:	
Post Industrial:	67%
Post Consumer:	10%
Total Recycled Content:	76%
SOIL/STAIN PROTECTION:	Protekt ² @
PRESERVATIVE PROTECTION:	Intersept@
INDOOR AIR QUALITY:	Green Label Plus #GLP0820, CDPH 01350

PRODUCT SPECIFICATIONS	IMPERIAL	METRIC
TUFTED YARN WEIGHT:	23 oz/yd ²	779.8 g/m ²
MACHINE GAUGE:	1/10 in	39.4 ends/cm
PILE HEIGHT:	0.134 in	3.4 mm
PILE THICKNESS:	0.072 in	1.8 mm
STITCHES:	10.00 /in	39.4 ends/10cm
PILE DENSITY:	11,189 oz/yd ³	414,885.6 g/m ³
TRAFFIC CLASSIFICATION:	Severe	
FIBER MODIFICATION RATIO:	1.9 to 2.2	
SIZE:	19.69 in x 19.69 in	50 cm x 50 cm

PERFORMANCE SPECIFICATIONS

Radiant Panel:	2(ASTM E-648) Passes
Smoke Density:	(ASTM E - 662) ≤ 450
Lightfastness:	(AATCC 16 - E) ≥ 4.0 @ 60 AFU's
Static:	(AATCC - 134) < 3.0 KV
Dimensional Stability:	AACHEN Din 54318 <.10%
Flammability:	Passes Methenamine Pill Test (DOC-FF1-70)
Standard Backing:	GlasBac®
Backing Options:	GlasBac®, GlasBac®RE, CushionBac Renew™

INSTALLATION

Installation Method	Monolithic
---------------------	------------

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see www.interface.com/disclaimer.