

# Interface

## DL905

|                          |                                       |
|--------------------------|---------------------------------------|
| PRODUCT NUMBER:          | 1502902500                            |
| PRODUCT CONSTRUCTION:    | Tufted Pattern Loop                   |
| STANDARD COLORLINE:      | 2                                     |
| YARN SYSTEM:             | 100% Recycled Content Nylon           |
| YARN MANUFACTURER:       | Aquafil                               |
| DYE METHOD:              | 100% Solution Dye                     |
| RECYCLED CONTENT:        |                                       |
| Post Industrial:         | 67%                                   |
| Post Consumer:           | 10%                                   |
| Total Recycled Content:  | 77%                                   |
| SOIL/STAIN PROTECTION:   | Protekt <sup>2</sup> @                |
| PRESERVATIVE PROTECTION: | Intersept@                            |
| INDOOR AIR QUALITY:      | Green Label Plus #GLP0820, CDPH 01350 |

| PRODUCT SPECIFICATIONS    | IMPERIAL                 | METRIC                     |
|---------------------------|--------------------------|----------------------------|
| TUFTED YARN WEIGHT:       | 23 oz/yd <sup>2</sup>    | 779.8 g/m <sup>2</sup>     |
| MACHINE GAUGE:            | 1/10 in                  | 39.4 ends/cm               |
| PILE HEIGHT:              | 0.139 in                 | 3.5 mm                     |
| PILE THICKNESS:           | 0.091 in                 | 2.3 mm                     |
| STITCHES:                 | 10.50 /in                | 41.3 ends/10cm             |
| PILE DENSITY:             | 9,099 oz/yd <sup>3</sup> | 337,388.9 g/m <sup>3</sup> |
| TRAFFIC CLASSIFICATION:   | Heavy                    |                            |
| FIBER MODIFICATION RATIO: | 1.9 to 2.2               |                            |
| SIZE:                     | 19.69 in x 19.69 in      | 50 cm x 50 cm              |

## PERFORMANCE SPECIFICATIONS

|                        |   |
|------------------------|---|
| Radiant Panel:         | 2(ASTM E-648) Passes                      |
| Smoke Density:         | (ASTM E - 662) ≤ 450                      |
| Lightfastness:         | (AATCC 16 - E) ≥ 4.0 @ 60 AFU's           |
| Static:                | (AATCC - 134) < 3.0 KV                    |
| Dimensional Stability: | AACHEN Din 54318 <.10%                    |
| Flammability:          | Passes Methenamine Pill Test (DOC-FF1-70) |
| Standard Backing:      | GlasBac®                                  |
| Backing Options:       | GlasBac®, GlasBac®RE, CushionBac Renew™   |

## INSTALLATION

|                     |                             |
|---------------------|-----------------------------|
| Installation Method | Monolithic, Non-Directional |
|---------------------|-----------------------------|

All product specifications reflect averages derived from product sample testing, are subject to normal manufacturing and testing tolerances and inherent pattern variances, and may be changed without notice. For more information about these and other important attributes of the product(s) described herein, including recycled content and product warranty information, please see [www.interface.com/disclaimer](http://www.interface.com/disclaimer).