

Specifications

Level Set Collection | Woodgrains

Style Name / Number	Textured Woodgrains - A004 Natural Woodgrains - A002
Product Construction	High Performance Luxury Vinyl Plank
Wear Layer Thickness	0.55 mm
Total Thickness	4.5 mm
Classification	EN 651 Class 33 (heavy contract) Class 42 (light industrial general)
Acoustic Layer	SOUND CHOICE™ Acoustic Backing
Finish	CERAMOR™ UV Stabilized Ceramic Bead Coating
Nominal Dimensions	25cm x 100cm

Performance

Critical Heat Flux	AS ISO 9239-1	>7kW/m ²
Smoke Rate	AS ISO 9239-1	<750%.min
Size, Tolerance	ISO 24342	<400 mm < 0.25 mm >400 mm < 0.35 mm
Dimensional Stability	ISO 23999	<0.25%
Thickness	ISO 24346	Average value + 0.20mm
Resistance to Light	ISO 105-B02	≥6
Resistance to Heat	ASTM F1514	ΔE < 8 avg Max
Resistance to Chemicals	EN-ISO 26987	Pass
VOC Test	ISO 10580	Pass
Flexibility	ISO 24344	Pass
Static Load	ASTM F970	≤0.005" with 1500 psi
Castor Chair	ISO 4918	Pass (25,000 cycles)
Abrasion Resistance	EN 660-2	<2 mm ³ / 100 cycles volume loss (T)
Thermal Conductivity	EN 12667	0.16 W/mK
Static Electrical	EN 1815	<2kV
Acoustic Impact Noise Reduction	ISO 140.8	ΔL _w = 16dB
Slip Resistance	AS 4586:2013	R10

Environmental

Ingredients & Life Cycle Impacts	Environmental Product Declaration
Sustainability Assessment	NSF/ANSI 332, Meets Certification Guidelines
LEED v4	Contributes to IEQ: <i>Low Emitting Materials</i> ; M&R: <i>EPD</i> and <i>EPR</i>
End of Life	Fully Recyclable LVT to Carpet Tile Backing Recycling

Technical Information

Installation	See Interface LVT Installation Guidelines online
Maintenance	See Interface LVT Maintenance Guidelines online
Reclamation	Recyclable through ReEntry®
Warranty	15 Year Limited Commercial Warranty
Installation Methods	Ashlar, Herringbone



Specifications

Level Set Collection | Stones

Style Name / Number	Natural Stones - A001 Textured Stones - A003
Product Construction	High Performance Luxury Vinyl Tile
Wear Layer Thickness	0.55 mm
Total Thickness	4.5 mm
Classification	EN 651 Class 33 (heavy contract) Class 42 (light industrial general)
Acoustic Layer	SOUND CHOICE™ Acoustic Backing
Finish	CERAMOR™ UV Stabilized Ceramic Bead Coating
Nominal Dimensions	50cm x 50cm

Performance

Critical Heat Flux	AS ISO 9239-1	>7kW/m ²
Smoke Rate	AS ISO 9239-1	<750%.min
Size, Tolerance	ISO 24342	<400 mm < 0.25 mm >400 mm < 0.35 mm
Dimensional Stability	ISO 23999	<0.25%
Thickness	ISO 24346	Average value + 0.20mm
Resistance to Light	ISO 105-B02	≥6
Resistance to Heat	ASTM F1514	ΔE < 8 avg Max
Resistance to Chemicals	EN-ISO 26987	Pass
VOC Test	ISO 10580	Pass
Flexibility	ISO 24344	Pass
Static Load	ASTM F970	≤0.005" with 1500 psi
Castor Chair	ISO 4918	Pass (25,000 cycles)
Abrasion Resistance	EN 660-2	<2 mm ³ / 100 cycles volume loss (T)
Thermal Conductivity	EN 12667	0.16 W/mK
Static Electrical	EN 1815	<2kV
Acoustic Impact Noise Reduction	ISO 140.8	ΔL _w = 16dB
Slip Resistance	AS 4586:2013	A001-02 - R9
	AS 4586:2013	A001-03 - R9
	AS 4586:2013	A003-01 - R9
	AS 4586:2013	A003-02 - R9
	AS 4586:2013	A003-03 - R9
	AS 4586:2013	A003-07 - R10

Environmental

Ingredients & Life Cycle Impacts	Environmental Product Declaration
Sustainability Assessment	NSF/ANSI 332, Meets Certification Guidelines
LEED v4	Contributes to IEQ: <i>Low Emitting Materials</i> ; M&R: <i>EPD</i> and <i>EPR</i>
End of Life	Fully Recyclable LVT to Carpet Tile Backing Recycling

Technical Information

Installation	See Interface LVT Installation Guidelines online
Maintenance	See Interface LVT Maintenance Guidelines online
Reclamation	Recyclable through ReEntry®
Warranty	15 Year Limited Commercial Warranty
Installation Methods	Non Directional, Ashlar, Brick, Monolithic, Quarter-Turn

