

Technical Specifications

Generic Type:	Needle Punched Felt Non-Woven
Underlay:	100% Recycled Polyester + Low Melting Fibre
Total Thickness:	3.2 mm Added to standard product thickness
Total weight:	700 g/m2 Added to standard product weight
Application:	With Glasbac Backing
Carton Size:	16 Tiles Per Carton
Tile Size:	500mm x 500mm – 1m x 1m – 1m x 250mm – 1m x 500mm
Backing Structure	CushionBacRE™
Installation Method	InterTac using a Roller Application

Performance Specifications

Area of Use	Depending on the product style
Dimensional Stability	Less than 0.2% variation
Anti-Static	AATCC134 < 3000Volts
Warranty	15 year limited warranty: <ul style="list-style-type: none"> ▪ Manufacturing defect ▪ Electrostatic propensity ▪ Excessive wear ▪ Dimensional stability ▪ Castor chair

Sustainability Specifications

Greenhouse Gas Emissions (GHG)	Qualifies for Interface's accredited Cool Carpet™ program option with zero net GHG emissions associated with the life cycle of the product.
Less Waste	Modular carpet creates about 85% less installation waste than broadloom.
Recyclable	GlasBac® & GlasBac®RE products qualify for recycling under Interface's optional ReEntry™ carpet reclamation program.