

# ReENTRY™ SPECIFICATION

## HOW TO SPECIFY ReENTRY™ FOR YOUR NEXT PROJECT?

Reduce your environmental footprint by specifying our carpet tile recycling program, ReEntry™, on your next refurbishment. Simply copy and paste the following content into your specification:

### INTERFACE ReENTRY™ CARPET RECYCLING SPECIFICATION

#### Description of Works

1. Removal of uplifted floorcoverings to be non-disruptive to the building environment.
2. Carpet removal contractor to supply ISPM quantity pallets and transport quantity shrink wrap.
3. Pallets to be in good condition with no broken, loose or missing boards.
4. All uplifted full carpet tiles or cut tiles to one third tile size are packed and shrink wrapped onto pallets.
5. Carpet tiles are stacked four (4) tiles per layer to a maximum of 120 layers (480 tiles) per pallet.
6. Every 40 layers a single full carpet tile is placed in the centre of the stack overlapping each of the four piles to lock in the separate stacks.
7. The tiles are shrink wrapped to the pallet in a manner that will provide the necessary strength to maintain stability during transport.
8. The pallets are collected by Interface at an agreed location.
9. The uplifted carpet tile is entered into Interface ReEntry™ program.

**Interface retains the right to alter this specification as required.**

**For more information go to [www.interface.com](http://www.interface.com)**

mission



**Mission Zero:**  
our promise to eliminate  
any negative impact our company  
may have on the environment  
by the year 2020.