

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031

P.O Box 240, North Melbourne, Victoria 3051


Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT									
Client : Interface 34 Airds	Australia Pty Ltd Road			Number : Date :	15-00329 31/07/201				
Minto NS	SW 2566		Print Date : 31/07/2015 Order Number : 37232						
Sample Descriptior	Loop pile carpet tile Colour : Grey/Dark Grey	Solution Dyed Ya	rn Nylon 6 /m2 On a Cusl	hionbac Backi	ng				
AS/ISO 9239.1-2003	Reaction to Fire Tests for Floorir Radiant Heat Source	ngs. Determinati	ion of the Bur	rning Behavio	our using a				
	Date of Sample Arrival 06/07/2015								
	Date Tested 31/07/2015								
	CHF Value	1	2	3	Mean				
	Length	3.8	4.5	4.5	4.3	kW/m²			
	Width	4.6	-	-	-	kW/m²			
	Smoke Value	1	2	3	Mean				
	Length	290	261	273	275	%.min			
	Width	272	-	-	-	%.min			
	Observations:								
	Melting				Yes				
	Melting Blistering				Yes Yes				

31261

6026

Australian Wool testing Authority Ltd Copyright - All Rights Reserved C



- Chemical Testing - Mechanical Testing - Performance & Approvals Testing

Accredited for compliance with ISO/IEC 17025

relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd

may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

: Accreditation No · Accreditation No : Accreditation No. Page 1 of 2

983

985

1356





APPROVED SIGNATORY



Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051

Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client :	Interface Australia Pty Ltd	Test Number	:	15-003299
	34 Airds Road	Issue Date	:	31/07/2015
	Minto NSW 2566	Print Date	:	31/07/2015
		Order Numbe	Order Number: 372	

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2001 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Each specimen was adhered to a substrate of 6mm thick fibre reinforced cement board using Roberts 656 adhesive and clamped prior to testing.

31261

6026

C Australian Wool testing Authority Ltd Copyright - All Rights Reserved



Accredited for compliance with ISO/IEC 17025 - Chemical Testing - Mechanical Testing - Performance & Approvals Testing

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

: Accreditation No. : Accreditation No. : Accreditation No. 983 985

1356

Page 2 of 2





SADM

APPROVED SIGNATORY