

SYDNEY CARPET LABORATORY

34 AIRDS ROAD, MINTO NSW 2566 - TEL: (02) 8706 4600 FAX: (02) 8706 4617

## TEST REPORT

Client: Interface Australia PTY LTD 34 Airds Road Minto NSW 2566 Test Report No: D11-16-022 Sample Received date: 29/03/2016 Test Date: 04/04/16 Report Date: 05/04/2016

Sample Description: Client Reference: "URBAN RETREAT COLLECTION 5 (UR103 & UR201)" 100% Solution Dyed Nylon 6 950g/m<sup>2</sup> on a Cushionbac RE Backing

AS ISO 9239.1 – 2003: Reaction to Fire Tests for Floorings – Determination of the Burning Behaviour Using a Radiant Heat Source

## **Results Summary**

CHF Value	Sample 1	Sample 2	Sample 3	Mean	
Length	4.2	-	-	-	kW/m <sup>2</sup>
Width	4.2	5.1	5.1	4.8	kW/m <sup>2</sup>

Smoke Value	Sample 1	Sample 2	Sample 3	Mean	
Length	204	-	-	-	%.min
Width	206	202	202	203	%.min
Melting				Yes	
Blistering				Yes	

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BS EN 13238:2001 at a temperature of  $23\pm2^{\circ}$ C and relative humidity of  $50\pm5\%$  for a minimum of 48 hours prior to testing.

Each Specimen was adhered to a substrate of 9mm thick fibre cement board using Intertac adhesive.

Accreditation No.2834.

Page 1 of 9

Accredited for compliance with ISO/IEC 17025.

The results of the test, calibrations and/or measurements included in this document are traceable to Australian/ International Standards. This report may not be reproduced except in full and shall be rendered void if amended or altered.

This document may not be used in any form without prior consent. The results on this report are related only to the items tested.