

Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031

P.O Box 240, North Melbourne, Victoria 3051


Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT							
Client : Interface 34 Airds F Minto NS ¹			lssue Print	Number : e Date : Date : r Number :	15-00330 31/07/201 31/07/201 37232	5	
Sample Description	Loop pile carpet tile Colour : Grey	ection 2 - B702" 6 Solution Dyed Ya nsity : 610g/n	rn Nylon 6 n2 On a Cushi	ionbac backin	g		
AS/ISO 9239.1-2003	Reaction to Fire Tests for Floo Radiant Heat Source	rings. Determinati	ion of the Bur	ning Behavic	our using a		
	Date of Sample Arrival			06/07/2015			
	Date Tested		31/07/2015				
	CHF Value	1	2	3	Mean		
	Length	3.4	4.5	3.6	3.8	kW/m²	
	Width	3.9	-	-	-	kW/m²	
	Smoke Value	1	2	3	Mean		
	Length	218	215	229	221	%.min	
	Width	230	-	-	-	%.min	
	Observations:						
	Melting				Yes		
	Blistering				Yes		
	Penetration of flame through to s	substrate			Yes		

31273

6028

Australian Wool testing Authority Ltd Copyright - All Rights Reserved C



Accredited for compliance with ISO/IEC 17025 - Chemical Testing - Mechanical Testing - Performance & Approvals Testing

relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd

may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

: Accreditation No · Accreditation No : Accreditation No. Page 1 of 2

983

985

1356



MICHAEL A. JACKSON B.Sc.(Hons)







Australian Wool Testing Authority Ltd - trading as AWTA Product Testing A.B.N 43 006 014 106 1st Floor, 191 Racecourse Road, Flemington, Victoria 3031 P.O Box 240, North Melbourne, Victoria 3051

Phone (03) 9371 2400 Fax (03) 9371 2499

TEST REPORT

Client :	Interface Australia Pty Ltd	Test Number :	15-003301
	34 Airds Road	Issue Date :	31/07/2015
	Minto NSW 2566	Print Date :	31/07/2015
		Order Number :	37232

The test results relate to the behaviour of the test specimens of a product under the particular conditions of the test, they are not intended to be sole criterion for assessing the potential fire hazard of the product in use.

Sample was conditioned in accordance with BSEN 13238:2001 at a temperature of 23±2°C and relative humidity of 50±5% for a minimum of 48 hours prior to testing.

Each specimen was adhered to a substrate of 6mm thick fibre reinforced cement board using Roberts 656 adhesive and clamped prior to testing.

31273

6028

C Australian Wool testing Authority Ltd Copyright - All Rights Reserved




Chemical Testing
Mechanical Testing
Performance & Approvals Testing

Accredited for compliance with ISO/IEC 17025

Samples and their identifying descriptions have been provided by the client unless otherwise stated. AWTA Ltd makes no warranty, implied or otherwise, as to the source of the tested samples. The above test results relate only to the sample or samples tested. This document shall not be reproduced except in full and shall be rendered void if amended or altered. This document, the names AWTA Product Testing and AWTA Ltd may be used in advertising providing the content and format of the advertisement have been approved by the Managing Director of AWTA Ltd.

: Accreditation No. : Accreditation No. : Accreditation No.

983 985 1356





SADM

APPROVED SIGNATORY