

## NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Visual Code™ Collection - Circuit Board

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Visual Code™ Collection - Circuit Board
Туре	Tapestry Tufted Patterned Structured Loop Pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	Graphlex <sup>®</sup>
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	7.7 mm $\pm$ 0.5 mm
Size	25 x 100 cm standard size, 3m <sup>2</sup> per box
Colourway	9280001 Orange Circuit 9280002 Yellow Circuit
	9280003 Green Circuit 9280004 Teal Circuit
	9280005 Blue Circuit 9280006 Purple Circuit
	9280007 Magenta Circuit 9280008 Red Circuit
Method of laying	Ashlar & Herringbone Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

