



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## NY+LON Streets - Old Street

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	N/a. Carpet tiles to be adhered direct to the subfloor.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	NY+LON Streets - Old Street			
<b>Type</b>	Tufted Patterned Structured Loop Pile			
<b>Yarn</b>	100% Solution Dyed Nylon contains recycled content			
<b>Standard Backing</b>	CQuest™Bio			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC1			
<b>Total Thickness</b>	6.0 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm standard size			
<b>Colourway</b>	9442001 Concrete Grid	9442002 Brown Grid	9442003 Iron Grid	9442004 Steel Grid
	9442005 Metal Grid	9442006 Graphite Grid	9442007 Slate Grid	9442008 Black Grid
<b>Method of laying</b>	Ashlar, Monolithic and Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465