

Visual Code™ Collection - Stitchery

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.	
Base	Please refer to Interface installation guide for details of suitability.	
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.	
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.	
Carpet Tiles		
Manufacturer	Interface	
Product Reference	Visual Code™ Collection - Stitchery	
Type	Tufted Patterned Structured Loop Pile	
Yarn	100% Recycled Solution Dyed Nylon	
Standard Backing	Graphlex®	
BS EN 1307 classification		
Category	Type 1	
Level of use class	Heavy Contract, class 33	
Luxury rating class	LC1	
Total Thickness	5.8 mm ± 0.5 mm	
Size	25 x 100 cm standard size, 5m ² per box	
Colourway	9281001 Nickel Stitchery	9281002 Iron Stitchery
	9281003 Grey Stitchery	9281004 Graphite Stitchery
	9281005 Flint Stitchery	9281006 Charcoal Stitchery
	9281007 Slate Stitchery	9281008 Black Stitchery
Method of laying	Ashlar & Herringbone Install using TacTiles® for a glue-free installation	

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#) For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465