



Collect

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Collect
Type	Pattern loop pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	7.9 mm ± 0.5 mm
Size	50 x 50 cm - 4 m ² Box
Colourway	302602 Sensify 302603 Allure 302604 Enrich 302605 Purity 302606 Attraction 302607 Captivate 302608 Filter 302609 Filter 302610 Magnetize
Method of laying	Monolithic. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690