



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Common Theme 102

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
<b>Base</b>	Please refer to Interface installation guide for details of suitability.
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.
<b>Carpet Tiles</b>	
<b>Manufacturer</b>	Interface
<b>Product Reference</b>	Common Theme 102
<b>Type</b>	Structured loop pile
<b>Yarn</b>	100% Solution Dyed Nylon contains recycled content
<b>Standard Backing</b>	Graphlex®
<b>BS EN 1307 classification</b>	
<b>Category</b>	Type 1
<b>Level of use class</b>	Heavy Contract, class 33
<b>Luxury rating class</b>	LC2
<b>Total Thickness</b>	7.4 mm ± 0.5 mm
<b>Size</b>	50 x 50 cm - 4 m <sup>2</sup> Box
<b>Colourway</b>	342001 Onyx      342002 Slate      342004 Pewter      342005 Steel
<b>Method of laying</b>	Ashlar, Quarter Turn. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690