



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Conscient

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.	
Base	Please refer to Interface installation guide for details of suitability.	
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.	
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.	
Carpet Tiles		
Manufacturer	Interface	
Product Reference	Conscient	
Type	Tufted Patterned Structured Tip Sheared Pile	
Yarn	100% Solution Dyed Nylon, 62.5% Biobased	
Standard Backing	CQuest™Bio	
BS EN 1307 classification		
Category	Type 1	
Level of use class	Heavy Contract, class 33	
Luxury rating class	LC2	
Total Thickness	5.8 mm ± 0.5 mm	
Size	50 x 50 cm standard size, 5m ² per box	
Colourway	4195001 Trace	4195004 Refined
	4195002 Factor	4195005 Element
	4195003 Emission	4195006 Fragment
Method of laying	Non Directional Install using TacTiles® for a glue-free installation	

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#) For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465