



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Elevation III

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Elevation III			
<b>Type</b>	Microtufted loop pile			
<b>Yarn</b>	100% Recycled Solution Dyed Nylon			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC1			
<b>Total Thickness</b>	4.6 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm - 5 m <sup>2</sup> Box			
<b>Colourway</b>	671401 Colletino	671402 Brocatello	671403 Palissandra	671404 Cioccolato
	671405 Fior Di Pesco	671406 Ceppo Di Gre	671407 Grigio Nilo	671408 Portoro
	671409 Carrara	671410 Jura	671411 Valdeorras	671412 Nero Maquina
	671413 Botticino	671414 Romano Classico	671415 Crema Luna	671416 Opale Naturale
	671417 Cipollino	671418 Aqua Marina	671419 Azuro Cielo	671420 Zircona
<b>Method of laying</b>	Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690