



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Elevation III

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
<b>Base</b>	Please refer to Interface installation guide for details of suitability.
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.
<b>Carpet Tiles</b>	
<b>Manufacturer</b>	Interface
<b>Product Reference</b>	Elevation III
<b>Type</b>	Microtufted loop pile
<b>Yarn</b>	100% Recycled Solution Dyed Nylon
<b>Standard Backing</b>	Graphlex®
<b>BS EN 1307 classification</b>	
<b>Category</b>	Type 1
<b>Level of use class</b>	Heavy Contract, class 33
<b>Luxury rating class</b>	LC1
<b>Total Thickness</b>	4.4 mm ± 0.5 mm
<b>Size</b>	50 x 50 cm - 5 m <sup>2</sup> Box
<b>Colourway</b>	4199001 Colletino 4199002 Brocatello 4199003 Palissandra 4199004 Cioccolato 4199005 Fior Di Pesco 4199006 Ceppo Di Gre 4199007 Grigio Nilo 4199008 Portoro 4199009 Carrara 4199010 Jura 4199011 Valdeorras 4199012 Nero Maquina 4199013 Botticino 4199014 Romano Classico 4199015 Crema Luna 4199016 Opale Naturalea 4199017 Cipollino 4199018 Aqua Marina 4199019 Azuro Cielo 4199020 Zircona
<b>Method of laying</b>	Quarter Turn. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465