



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Equal Measure 553

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
<b>Base</b>	Please refer to Interface installation guide for details of suitability.
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.
<b>Carpet Tiles</b>	
<b>Manufacturer</b>	Interface
<b>Product Reference</b>	Equal Measure 553
<b>Type</b>	Cut and loop pile
<b>Yarn</b>	100% Recycled Solution Dyed Nylon
<b>Standard Backing</b>	Graphlex®
<b>BS EN 1307 classification</b>	
<b>Category</b>	Type 1
<b>Level of use class</b>	Heavy Contract, class 33
<b>Luxury rating class</b>	LC4
<b>Total Thickness</b>	9.6 mm ± 0.5 mm
<b>Size</b>	25 x 100 cm - 3 m <sup>2</sup> Box
<b>Colourway</b>	334301 Cobblestone Blvd. 334302 Park Blvd. 334303 Main Blvd. 334304 Hill Blvd. 334305 Broad Blvd. 334306 Market Blvd. 334307 Union Blvd. 334308 Oldtown Blvd.
<b>Method of laying</b>	Herringbone, Ashlar. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690