

Employ Dimensions

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Employ Dimensions			
Type	Tufted Patterned Level Loop Pile			
Yarn	100% Solution Dyed Nylon			
Standard Backing	Graphlex®			
Backing Options	SONE® & ReCushion Bac			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	5.5 mm ± 0.5 mm			
Size	25 x 100 cm standard size, 5m ² per box			
Colourway	4271003 Connect	4271005 Time	4271004 Parallel	4271006 Scale
	4271001 Volume	4271008 Measure	4271002 Surface	4271007 Line
	4271010 Object	4271009 Segment		
Method of laying	Ashlar, Herringbone Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#) For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465