



## Employ Loop

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Employ Loop			
<b>Type</b>	Level loop pile			
<b>Yarn</b>	100% Solution Dyed Nylon			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC1			
<b>Total Thickness</b>	5.5 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm - 5 m <sup>2</sup> Box			
<b>Colourway</b>	4197001 Raffia	4197002 Truffle	4197003 Shadow	4197004 Caramel
	4197005 Praline	4197006 Shale	4197007 Nutmeg	4197008 Fountain
	4197009 Jet	4197010 Rye	4197011 Cirrus	4197012 Atlantic
	4197013 Crystal	4197014 Tropical	4197015 Kiwi	4197016 Nordic
	4197017 Peacock	4197018 Eden	4197019 Baring	4197020 Oxford
	4197021 Clementine	4197022 Sapphire	4197023 Lavender	4197024 Salsa
<b>Method of laying</b>	Quarter Turn, Monolithic. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465