



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Equilibrium

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.		
<b>Base</b>	Please refer to Interface installation guide for details of suitability.		
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.		
<b>Carpet Tiles</b>			
<b>Manufacturer</b>	Interface		
<b>Product Reference</b>	Equilibrium		
<b>Type</b>	Structured loop pile		
<b>Yarn</b>	100% Recycled Solution Dyed Nylon		
<b>Standard Backing</b>	Graphlex®		
<b>BS EN 1307 classification</b>			
<b>Category</b>	Type 1		
<b>Level of use class</b>	Heavy Contract, class 33		
<b>Luxury rating class</b>	LC2		
<b>Total Thickness</b>	7.3 mm ± 0.5 mm		
<b>Size</b>	50 x 50 cm - 4 m <sup>2</sup> Box		
<b>Colourway</b>	304208 Consistency	304293 Contentment	304207 Continuity
	304209 Equality	304286 Equation	304295 Harmony
	304281 Mobility	304296 Moderation	304205 Persistence
	304289 Serenity	304287 Symmetry	304298 Uniformity
<b>Method of laying</b>	Ashlar, Monolithic, Quarter Turn. Install using TacTiles® for a glue-free installation		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465

