



Equilibrium

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Equilibrium			
Type	Structured loop pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	7.5 mm ± 0.5 mm			
Size	50 x 50 cm - 4 m ² Box			
Colourway	304262 Constant	304271 Parity	304281 Mobility	304282 Fluctuation
	304286 Equation	304287 Symmetry	304289 Serenity	304293 Contentment
	304295 Harmony	304296 Moderation	304298 Uniformity	304200 Balance
	304201 Correlation	304202 Vitality	304203 Simplicity	304204 Entity
	304205 Persistence	304206 Analogy	304207 Continuity	30408 Consistency
	304209 Equality	304210 Unity	304211 Accuracy	304212 Proportion
	304213 Similarity	304214 Classification	304215 Integrity	304216 Arrangement
	304217 Ability	304218 Coincidence		
Method of laying	Ashlar, Monolithic, Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690