



Fastforward

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Fastforward
Type	Cut pile tufted
Yarn	100% Solution Dyed Nylon contains recycled content
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	5.2 mm ± 0.5 mm
Size	50 x 50 cm - 5 m ² Box
Colourway	608120 Steel 608121 Granite 608123 Coffee 608134 Vermillion 608135 Pumpkin 608136 Plum 608137 Wave 608138 Mastic
Method of laying	Ashlar, Non Directional, Brick. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690