

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Global Change - Ground

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Global Change - Ground			
Туре	Tufted patterned structured loop pile			
Yarn	100% Solution Dyed Nylon contains recycled content			
Standard Backing	Graphlex [®]			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	7.0 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	9083001 Daylight	9083002 Desert Shadow	9083003 Evening Dusk	9083004 Morning Mist
	9083005 Fawn	9083006 Eclipse		
Method of laying	Brick and Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 01274 690690

