



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Heuga 493

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Heuga 493			
Type	Level loop pile			
Yarn	100% Polypropylene			
Standard Backing	Graphlar®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	6 mm ± 0.5 mm			
Size	50 x 50 cm - 5 m ² Box			
Colourway	9301 Lava	9302 Tamarind	9303 Orchid	9305 Basalt
	9306 Teak	9308 Deepsea	9309 Lead	9311 Parade
	9314 Gravel	9315 Bluebeard	9316 Rainforest	9319 True Blue
	9320 Basil			
Method of laying	Monolithic, Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690