



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Heuga 530 II

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Heuga 530 II			
<b>Type</b>	Structured loop pile			
<b>Yarn</b>	100% Recycled Nylon			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC2			
<b>Total Thickness</b>	6.4 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm - 5 m <sup>2</sup> Box			
<b>Colourway</b>	4288001 Gravel	4288002 Pebble	4288003 Stone	4288004 Carbon
	4288005 Silver	4288006 Dolphin	4288007 Basalt	4288008 Black
	4288009 Silk Grey	4288010 Cashmere	4288011 Bark	4288012 Taupe
	4288013 Golden Yellow	4288014 Terracotta	4288015 Dusty Rose	4288016 Frosted Lilac
	4288017 Dove Blue	4288018 Indigo	4288019 Blueberry	4288020 Blue Moon
	4288021 Ginger	4288022 Sage	4288023 Mint	4288024 Forest
<b>Method of laying</b>	Monolithic, Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465