

## Heuga 580

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Heuga 580			
<b>Type</b>	Level loop pile			
<b>Yarn</b>	100% Nylon			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC1			
<b>Total Thickness</b>	5.8 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm - 5 m <sup>2</sup> Box			
<b>Colourway</b>	5101 Nickel	5102 Elephant	5103 Granite	5104 Twilight
	5105 Grey	5106 Oyster	5107 Onyx	5108 Black
	5109 Quartz	5110 Zircon	5111 Earth	5112 Ebony
	5113 Flax	5114 Timber	5115 Cacao	5116 Wenge
	5117 Rosewood	5118 Sisal	5119 Teak	5120 Chocolate
	5121 Lemon Grass	5122 Ginger	5123 Mahogany	5124 Chilli Chocolate
	5125 Curcuma	5126 Chili	5127 Tandoori	5128 Opera
	5129 Magenta	5130 Firecracker	5131 Massai Red	5132 Aubergine
	5133 Lavender	5134 Velvet	5135 Mauve	5136 Blackcurrant
	5137 Sky	5138 Cornflower	5139 Opal	5140 Lobelia
	5141 Leak Blue	5142 Blue Moon	5143 Blueberry	5144 Ultra Marine
	5145 Santorin	5146 Crete	5147 Deep River	5148 Indigo
	5149 Lagoon	5150 Curacao	5151 Reef	5152 Antilles
	5153 Apple	5154 Poison	5155 Green	5156 Windsor Green
	5157 Lime	5158 Kiwi	5159 Palm	5160 The Shire

**Method of laying**

Monolithic, Quarter Turn.  
Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465