



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Heuga 727

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Heuga 727
Type	Level loop pile
Yarn	100% Nylon
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	5.1 mm ± 0.5 mm
Size	50 x 50 cm - 5 m ² Box
Colourway	672701 Platin(SD) 672702 Elephant(SD) 672703 Graphite(SD) 672704 Coal(SD) 672705 Dust(SD) 672706 Pebbles(SD) 672707 Panther(SD) 672708 Onyx(SD) 672709 Silver(SD) 672710 Copra(SD) 672711 Cotton(SD) 672712 Nutmeg(SD) 672713 Oyster (SD) 672714 Linen(SD) 672715 Camel(SD) 672716 Mocha(PD) 672717 Sunflower(PD) 672718 Paprika(SD) 672719 Hot Pepper(SD) 672720 Chocolate(SD) 672721 Cayenne(PD) 672722 Opera(SD) 672723 Amaryllis(SD) 672724 Mauve(PD) 672725 Pashmina(PD) 672726 Fuchsia(PD) 672727 Hot Pink(PD) 672728 Dark Orchid(PD) 672729 Lilac(SD) 672730 Midnight(SD) 672731 Bilberry(SD) 672732 Blackcurrant(PD) 672733 Mercury(SD) 672734 Lavender(SD) 672735 Lobelia(SD) 672736 Blue Riband(SD) 672737 Lagoon(PD) 672738 Ocean(PD) 672739 Cobalt(SD) 672740 Real Blue(PD) 672741 Aegean Blue(PD) 672742 Spring(PD) 672743 Green(PD) 672744 Emerald(PD) 672745 Lemonade(PD) 672746 Pistacchio(PD) 672747 Olive(PD) 672748 Jungle(PD)
Method of laying	Monolithic, Quarter Turn. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465