



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Human Nature 810

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Human Nature 810			
Type	Pattern loop pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC3			
Total Thickness	9.6mm ± 0.5 mm			
Size	25 x 100 cm - 3m ² Box			
Colourway	308051 Flint	308052 Nickel	308053 Slate	308054 Limestone
	308055 Pumice	308056 Shale	308057 Earth	308058 Travertine
Method of laying	Ashlar, Herringbone. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690