



Human Nature 820

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Human Nature 820
Type	Cut and loop pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	7 mm ± 0.5 mm
Size	25 x 100 cm - 4.5 m ² Box
Colourway	308063 Slate 308062 Nickel 308066 Shale 308064 Limestone
Method of laying	Ashlar, Herringbone. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465