



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Ice Breaker

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.										
Base	Please refer to Interface installation guide for details of suitability.										
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.										
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.										
Carpet Tiles											
Manufacturer	Interface										
Product Reference	Ice Breaker										
Type	Tufted Patterned Structured Loop Pile										
Yarn	100% Solution Dyed Nylon, contains recycled content										
Standard Backing	Graphlex®										
BS EN 1307 classification											
Category	Type 1										
Level of use class	Heavy Contract, class 33										
Luxury rating class	LC2										
Total Thickness	6.6 mm ± 0.5 mm										
Size	50 x 50 cm standard size, 5m ² per box										
Colourway	<table border="0"> <tr> <td>4282001 Concrete</td> <td>4282002 Granite</td> </tr> <tr> <td>4282003 Jetmist</td> <td>4282004 Chalk</td> </tr> <tr> <td>4282005 Gritstone</td> <td>4282006 Obsidian</td> </tr> <tr> <td>4282007 Claystone</td> <td>4282008 Siltstone</td> </tr> <tr> <td>4282009 Quarry</td> <td></td> </tr> </table>	4282001 Concrete	4282002 Granite	4282003 Jetmist	4282004 Chalk	4282005 Gritstone	4282006 Obsidian	4282007 Claystone	4282008 Siltstone	4282009 Quarry	
4282001 Concrete	4282002 Granite										
4282003 Jetmist	4282004 Chalk										
4282005 Gritstone	4282006 Obsidian										
4282007 Claystone	4282008 Siltstone										
4282009 Quarry											
Method of laying	Non Directional Install using TacTiles® for a glue-free installation										

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#) For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465