



## Infuse

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Infuse			
<b>Type</b>	Pattern loop pile			
<b>Yarn</b>	100% Solution Dyed Nylon contains recycled content			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC2			
<b>Total Thickness</b>	6.6 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm - 4 m <sup>2</sup> Box			
<b>Colourway</b>	333450 Ash/Lupin	333451 Ash/Almond	333452 Clay/Lime	333453 Clay/Cobalt
	333454 Graphite/Ruby	333455 Graphite/Pine	333456 Barley/Honey	333457 Barley/Truffle
	333458 Mink/Duck Egg	333459 Mink/Herb	333460 Jubilee/Plum	333461 Jubilee/Jade
<b>Method of laying</b>	Ashlar, Brick. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690