



Infuse

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Infuse
Type	Pattern loop pile
Yarn	100% Solution Dyed Nylon contains recycled content
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	6.6 mm ± 0.5 mm
Size	50 x 50 cm - 4 m ² Box
Colourway	333450 Ash/Lupin 333451 Ash/Almond 333452 Clay/Lime 333453 Clay/Cobalt 333454 Graphite/Ruby 333455 Graphite/Pine 333456 Barley/Honey 333457 Barley/Truffle 333458 Mink/Duck Egg 333459 Mink/Herb 333460 Jubilee/Plum 333461 Jubilee/Jade
Method of laying	Ashlar, Brick. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690