



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Mod Café

| | |
|----------------------------------|--|
| Location | Heavy use areas. Office, retail, hospitality, leisure and educational areas. |
| Base | Please refer to Interface installation guide for details of suitability. |
| Preparation | Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. |
| Fabricated Underlay | Should be laid where required over existing timber bases. |
| Carpet Tiles | |
| Manufacturer | Interface |
| Product Reference | Mod Café |
| Type | Pattern loop pile |
| Yarn | 100% Recycled Solution Dyed Nylon |
| Standard Backing | Graphlex® |
| BS EN 1307 classification | |
| Category | Type 1 |
| Level of use class | Heavy Contract, class 33 |
| Luxury rating class | LC2 |
| Total Thickness | 8.5 mm ± 0.5 mm |
| Size | 50 x 50 cm - 4 m ² Box |
| Colourway | 303301 Star Linen 303302 Star Flannel 303303 Star Charcoal 303304 Star Black 303305 Star Brown 303306 Star Natural 303307 Star Raffia 303308 Star Sisal |
| Method of laying | Monolithic. Install using TacTiles® for a glue-free installation |

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690