

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Multichrome

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Multichrome			
Туре	Tufted Patterned Structured Loop Pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	Graphlex [®]			
BS EN 1307 classific	ation			
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	7.2 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	4262001 Cream Chrome 4262005 Silver Chrome 4262009 Very Berry Chrome 4262013 Meadow Chrome	4262002 Caraway Chrome 4262006 Platinum Chrome 4262010 Lilac Chrome 4262014 Spun Chrome	Chrome	4262004 Millstone Chrome 4262008 Black Chrome 4262012 Pacific Chrome 4262016 Gerbera Chrome
Method of laying	Monolithic Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 01274 690690

Interface®