



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

New Dimensions II

| | | | | |
|----------------------------------|---|----------------|----------------|------------------|
| Location | Heavy use areas. Office, retail, hospitality, leisure and educational areas. | | | |
| Base | Please refer to Interface installation guide for details of suitability. | | | |
| Preparation | Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. | | | |
| Fabricated Underlay | Should be laid where required over existing timber bases. | | | |
| Carpet Tiles | | | | |
| Manufacturer | Interface | | | |
| Product Reference | New Dimensions II | | | |
| Type | Pattern loop pile | | | |
| Yarn | 100% Solution Dyed Nylon contains recycled content | | | |
| Standard Backing | Graphlex® | | | |
| BS EN 1307 classification | | | | |
| Category | Type 1 | | | |
| Level of use class | Heavy Contract, class 33 | | | |
| Luxury rating class | LC1 | | | |
| Total Thickness | 6.7 mm ± 0.5 mm | | | |
| Size | 50 x 50 cm - 4 m ² Box | | | |
| Colourway | 396131 Flax | 396132 Onyx | 396133 Granary | 396134 Denim |
| | 396135 Lagoon | 396136 Sangria | 396137 Regent | 396138 Gun Metal |
| Method of laying | Non Directional. Install using TacTiles® for a glue-free installation | | | |

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690