



## Near & Far 400

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Near & Far 400			
<b>Type</b>	Structured loop pile			
<b>Yarn</b>	100% Recycled Solution Dyed Nylon			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC2			
<b>Total Thickness</b>	6.9 mm ± 0.5 mm			
<b>Size</b>	25 x 100 cm - 4 m <sup>2</sup> Box			
<b>Colourway</b>	333401 Felt	333402 Mineral	333403 Driftwood	333404 Linen
	333405 Shale	333406 Hemp	333407 Walnut	333408 Wheat
<b>Method of laying</b>	Herringbone, Ashlar. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690