



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Near & Far 400

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
<b>Base</b>	Please refer to Interface installation guide for details of suitability.
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.
<b>Carpet Tiles</b>	
<b>Manufacturer</b>	Interface
<b>Product Reference</b>	Near & Far 400
<b>Type</b>	Structured loop pile
<b>Yarn</b>	100% Recycled Solution Dyed Nylon
<b>Standard Backing</b>	Graphlex®
<b>BS EN 1307 classification</b>	
<b>Category</b>	Type 1
<b>Level of use class</b>	Heavy Contract, class 33
<b>Luxury rating class</b>	LC2
<b>Total Thickness</b>	6.9 mm ± 0.5 mm
<b>Size</b>	25 x 100 cm - 4 m <sup>2</sup> Box
<b>Colourway</b>	333401 Felt      333402 Mineral      333403 Driftwood      333404 Linen 333405 Shale      333406 Hemp      333407 Walnut      333408 Wheat
<b>Method of laying</b>	Herringbone, Ashlar. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690