



Narratives 230

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Narratives 230			
Type	Structured loop pile			
Yarn	100% Solution Dyed Nylon contains recycled content			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC3			
Total Thickness	10.2 mm ± 0.5 mm			
Size	25 x 100 cm - 3 m ² Box			
Colourway	334401 Fennel	334402 Ginger	334403 Wasabi	334404 Chai
	334405 Ginseng	334406 Sesame	334407 Darjeeling	334408 Oolong
Method of laying	Herringbone, Ashlar. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690