



# NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## On Line

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	On Line			
<b>Type</b>	Pattern loop pile			
<b>Yarn</b>	100% Recycled Solution Dyed Nylon			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC2			
<b>Total Thickness</b>	7.1 mm ± 0.5 mm			
<b>Size</b>	25 x 100 cm - 4 m <sup>2</sup> Box			
<b>Colourway</b>	333101 Bis cuit	333102 Mushroom	333103 Mustard	333104 Sage
	333105 Canary	333106 Cloud	333107 Pewter	333108 Mandarin
	333109 Pepper	333110 Lime	333111 Topaz	333112 Ink
	333113 Forest	333114 Azure	333115 Lapis	333116 Poppy
	333117 Dune	333118 Titanium	333119 Sable	333120 Granite
	333121 Pigeon	333122 Aquamarine	333123 Cobalt	333124 Magenta
<b>Method of laying</b>	Ashlar, Herringbone. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690