



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

On Line

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	On Line			
Type	Pattern loop pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	7.1 mm ± 0.5 mm			
Size	25 x 100 cm - 4 m ² Box			
Colourway	333101 Bis cuit	333102 Mushroom	333103 Mustard	333104 Sage
	333105 Canary	333106 Cloud	333107 Pewter	333108 Mandarin
	333109 Pepper	333110 Lime	333111 Topaz	333112 Ink
	333113 Forest	333114 Azure	333115 Lapis	333116 Poppy
	333117 Dune	333118 Titanium	333119 Sable	333120 Granite
	333121 Pigeon	333122 Aquamarine	333123 Cobalt	333124 Magenta
Method of laying	Ashlar, Herringbone. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690

Interface Europe Ltd., Shelf Mills, Shelf, Halifax, West Yorkshire HX3 7PA Tel: 01274 690690,
Customer Services Tel: 08705 304030, Email: enquiries@interface.com www.interface.com

Interface®