



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

On Line

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	On Line			
Type	Pattern loop pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.9 mm ± 0.5 mm			
Size	25 x 100 cm - 5 m ² Box			
Colourway	7335001 Biscuit	7335002 Mushroom	7335003 Mustard	7335004 Sage
	7335005 Canary	7335006 Cloud	7335007 Pewter	7335008 Mandarin
	7335009 Pepper	7335010 Lime	7335015 Topaz	7335016 Ink
	7335017 Forest	7335018 Azure	7335019 Lapis	7335020 Poppy
	7335021 Dune	7335022 Titanium	7335023 Sable	7335024 Granite
	7335025 Pigeon	7335006 Aquamarine	7335027 Cobalt	7335028 Magenta
Method of laying	Ashlar, Herringbone. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT
Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

Interface®