



## Output Micro

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
<b>Base</b>	Please refer to Interface installation guide for details of suitability.			
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.			
<b>Carpet Tiles</b>				
<b>Manufacturer</b>	Interface			
<b>Product Reference</b>	Output Micro			
<b>Type</b>	Microtufted loop pile			
<b>Yarn</b>	100% Solution Dyed Nylon			
<b>Standard Backing</b>	Graphlex®			
<b>BS EN 1307 classification</b>				
<b>Category</b>	Type 1			
<b>Level of use class</b>	Heavy Contract, class 33			
<b>Luxury rating class</b>	LC1			
<b>Total Thickness</b>	4.8 mm ± 0.5 mm			
<b>Size</b>	50 x 50 cm - 5 m <sup>2</sup> Box 100 m <sup>2</sup> PL			
<b>Colourway</b>	4220001 Denim	4220002 Admiral	4220003 Silver	4220004 Flint
	4220005 Papyrus	4220006 Hopsack	4220007 Flax	4220008 Graphite
<b>Method of laying</b>	Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465