

Polichrome Solid

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Polichrome Solid			
Type	Tufted Frieze Cut Pile			
Yarn	100% Nylon			
Standard Backing	Graphlex®			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC4			
Total Thickness	7.1 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	4266001 Metal	4266002 Mousey	4266003 Cloudburst	4266004 Liquorice
	4266005 Silk Grey	4266006 Cinder	4266007 Shiitake	4266008 Mole
	4266009 Waterfall	4266010 Distant	4266011 Daphne	4266012 Peridot
	4266013 Columbia	4266014 Powderblue	4266015 Blue Nights	4266016 Daiquiri
	4266017 Turtledove	4266018 Mimosa	4266019 Bubblegum	4266020 Viola
	4266021 Marzipan	4266022 Carrot	4266023 Grenadine	4266024 Malva
Method of laying	Monolithic Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465