



Series.1.101

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Series.1.101
Type	Level loop pile
Yarn	100% Solution Dyed Nylon contains recycled content
Standard Backing	Graphlex®
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	5.6 mm ± 0.5 mm
Size	50 x 50 cm - 5 m ² Box
Colourway	338410 Lapis 338411 Shale 338412 Opal 338413 Malachite 338414 Quartz 338415 Graphite 338416 Pewter 338417 Adobe
Method of laying	Quarter Turn, Monolithic. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690