



## Silver Lining 920

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
<b>Base</b>	Please refer to Interface installation guide for details of suitability.
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
<b>Fabricated Underlay</b>	Should be laid where required over existing timber bases.
<b>Carpet Tiles</b>	
<b>Manufacturer</b>	Interface
<b>Product Reference</b>	Silver Lining 920
<b>Type</b>	Pattern loop pile
<b>Yarn</b>	100% Recycled Solution Dyed Nylon
<b>Standard Backing</b>	Graphlex®
<b>BS EN 1307 classification</b>	
<b>Category</b>	Type 1
<b>Level of use class</b>	Heavy Contract, class 33
<b>Luxury rating class</b>	LC2
<b>Total Thickness</b>	6.5 mm ± 0.5 mm
<b>Size</b>	25 x 100 cm - 5 m <sup>2</sup> Box
<b>Colourway</b>	7832001 Navy Line 7832002 Black Line 7832003 Charcoal Line 7832004 Graphite Line 7832005 Nickel Line 7832006 Grey Line 7832007 Stone Line 7832010 Beige Line 7832011 Taupe Line
<b>Method of laying</b>	Ashlar, Herringbone. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465