

**Visual Code™ Collection - Static Lines**

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.	
<b>Base</b>	Please refer to Interface installation guide for details of suitability.	
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.	
<b>Fabricated Underlay</b>	N/a. Carpet tiles to be adhered direct to the subfloor.	
<b>Carpet Tiles</b>		
<b>Manufacturer</b>	Interface	
<b>Product Reference</b>	Visual Code™ Collection - Static Lines	
<b>Type</b>	Tapestry Tufted Patterned Structured Loop Pile	
<b>Yarn</b>	100% Recycled Solution Dyed Nylon	
<b>Standard Backing</b>	Graphlex®	
<b>BS EN 1307 classification</b>		
<b>Category</b>	Type 1	
<b>Level of use class</b>	Heavy Contract, class 33	
<b>Luxury rating class</b>	LC2	
<b>Total Thickness</b>	7 mm ± 0.5 mm	
<b>Size</b>	25 x 100 cm standard size, 5m <sup>2</sup> per box	
<b>Colourway</b>	9276001 Steel Static	9276002 Pewter Static
	9276003 Lead Static	9276004 Granite Static
<b>Method of laying</b>	Ashlar & Herringbone Install using TacTiles® for a glue-free installation	

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#) For Maintenance instructions, click [here](#)

To obtain samples please call 01274 690690