

Visual Code™ Collection - Stitch Count

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.	
Base	Please refer to Interface installation guide for details of suitability.	
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.	
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.	
Carpet Tiles		
Manufacturer	Interface	
Product Reference	Visual Code™ Collection - Stitch Count	
Type	Tufted Patterned Structured Tip Sheared Pile	
Yarn	100% Recycled Solution Dyed Nylon	
Standard Backing	Graphlex®	
BS EN 1307 classification		
Category	Type 1	
Level of use class	Heavy Contract, class 33	
Luxury rating class	LC3	
Total Thickness	8.1 mm ± 0.5 mm	
Size	25 x 100 cm standard size, 5m ² per box	
Colourway	9279001 Nickel Count	9279002 Iron Count
	9279003 Grey Count	9279004 Graphite Count
	9279005 Flint Count	9279006 Charcoal Count
	9279007 Slate Count	9279008 Black Count
Method of laying	Ashlar & Herringbone Install using TacTiles® for a glue-free installation	

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#) For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465